



US 20040041807A1

(19) **United States**

(12) **Patent Application Publication**

Hornegger et al.

(10) **Pub. No.: US 2004/0041807 A1**

(43) **Pub. Date: Mar. 4, 2004**

(54) **METHOD FOR GENERATING A 3D IMAGE DATASET**

(76) Inventors: **Joachim Hornegger**, Baiersdorf (DE);
Joachim Reiss, Baiersdorf (DE)

Correspondence Address:
SCHIFF HARDIN & WAITE
6600 SEARS TOWER
233 S WACKER DR
CHICAGO, IL 60606-6473 (US)

(21) Appl. No.: **10/465,104**

(22) Filed: **Jun. 19, 2003**

(30) **Foreign Application Priority Data**

Jun. 19, 2002 (DE)..... 102 27 307.3

Publication Classification

(51) **Int. Cl.⁷** **G06T 15/00**

(52) **U.S. Cl.** **345/419**

(57) **ABSTRACT**

In a method for the generation of a 3D dataset from 2D x-ray datasets, the 2D data are forwarded from a customer to a 3D reconstruction center in which a calibration of the projection geometry ensues by means of a software package and/or a specialist. As a result a 3D volume dataset is calculates and made available to the customer.

METHOD FOR GENERATING A 3D IMAGE DATASET

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The invention concerns a method for generating a 3D dataset from 2D x-ray recordings that require elaborate calibrations of a C-arm system used to generate the 2D datasets. It is desirable for a reconstruction of this type to ensue on a standard computer that is networked with the x-ray installation, however, the 3D option is not available on many installations and an offline reconstruction cannot be done because no calibration data are available.

[0003] 2. Description of the Prior Art

[0004] Although methods exist to calculate the projection parameters from datasets obtained without calibration samples, they are not 100% dependable or may not be numerically possible under the circumstances, since the projections are recorded nonlinearly.

[0005] A Picture Archiving and Communication System (PACS) for the treatment of acquired image data and the visualization of volume data is described in the article "Three-Dimensional Medical Visualization Bound To Break The Limits Of Diagnostics And Treatment", by Leslie Versweyveld, Virtual Medical World Monthly, May 2001. Visualization refers to a class of algorithms that allow image data to be visualized on a monitor. For example, a volume renderer forms a 3D volume that can then be presented on a 2D monitor from a 2D image.

SUMMARY OF THE INVENTION

[0006] An object of the invention is to provide a method for the reconstruction of a 3D dataset for users of simple C-arm systems that are not equipped to derive such a 3D volume dataset as needed from 2D x-ray recordings. As used herein, a U.S.P.Q.2d x-ray recording means the x-ray image itself or a dataset representing the image.

[0007] This object is achieved in accordance with the invention in a method wherein the 2D recordings from a customer are forwarded to a 3D reconstruction center, in which a calibration of the projection geometry ensues by means of a software package and/or by a specialist, and as a result a 3D volume dataset is calculated and made available to the customer.

[0008] By the inventive relocation of the generation of a 3D dataset to a suitably equipped reconstruction center, every user of a C-arm system can have such a 3D dataset prepared as needed without the expensive and elaborate installation for the generation of a 3D dataset, by the customer sending the 2D x-ray recordings to the reconstruction central in various manners. In addition to the possibility to burn the data on a CD and to forward this and, if necessary, the 2D x-ray recording itself, through the mail to the reconstruction central, it is especially practical for the customer to be connected to the reconstruction central via the Internet, so that the customer can electronically transmit 2D datasets and download the desired results via the Internet.

[0009] As used herein, reconstruction means a class of algorithms that calculate the original data (i.e. before the

projection) from the projection data recorded from various directions. For example, the result of the 3D reconstruction from 2D projections is a volume dataset.

[0010] In addition to the possibility of the creation of a 3D volume (for example, in DICOM), the reconstruction center can create a video of the rendered dataset, or make specially rendered individual exposures of the 3D dataset available.

[0011] A software package and/or a specialist using this data effects a calibration of the project geometry in the reconstruction center, which can ensue in various manners:

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0012] Many physicians have, in their office or clinic, access to an x-ray imaging system which is capable of generating two-dimensional (2D) x-ray images or x-ray image datasets. For many everyday applications, such two dimensional x-ray images are sufficient for the physician's needs, however, occasionally the physician may have a need for making a diagnosis based on a three-dimensional image. Since a software package to produce such a three-dimensional image from multiple 2D projections is relatively expensive, it is not cost-justified for the physician to purchase such a package only for such occasional uses. In accordance with the invention, when the physician has a need for making a diagnosis based on a three dimensional image, the physician communicates multiple sets of 2D projection data, or possibly the x-ray images themselves, to a reconstruction center, which is remote from the location of the physician. The reconstruction center has the computational capability of generating a three-dimensional image from multiple 2D projection datasets. After the reconstruction center generates the three-dimensional image, the data representing this three-dimensional image are communicated back to the physician.

[0013] For generating the three-dimensional image, it is necessary to reference the respective 2D projections relative to each other, in terms of their spatial relationship (calibration). There are several techniques available for undertaking this step.

[0014] An autocalibration can ensue at the reconstruction center in such a manner that natural landmarks are automatically detected and point correspondences calculated with image processing methods (segmentation). The 3D coordinates of the points as well as the projection parameters (extrinsic and intrinsic camera parameters) are subsequently assessed.

[0015] In a further autocalibration, natural landmarks are manually detected and the point correspondences calculated with image processing methods (segmentation) at the reconstruction center. The 3D coordinates of the points as well as the projection parameters are again subsequently assessed.

[0016] In a third embodiment of an autocalibration, markers are applied to the patient when the 2D projections are obtained and these markers are automatically detected and the point correspondences calculated with image processing methods (segmentation) at the reconstruction center. The 3D coordinates of the points as well as the projection parameters (extrinsic and intrinsic camera parameters) are again subsequently assessed.

[0017] Calibration with a reference sample can also ensue, by a calibration sample with known 3D geometry being located together with the patient data in the exposure. The point features are automatically detected and the point correspondences are calculated. Again, the assessment of the project parameters ensues with known 3D geometry.

[0018] An advantage of the inventive method is that the customer is given the possibility to have a 3D volume dataset generated via the Internet, even without a 3D package. This is important for the presentation of interesting, scientific, and new medical applications. The inventive method, however, also will further the usage of 3D reconstruction from x-ray recordings, and enable wide as well as cost-effective applications. In addition, the inventive method provides the opportunity to effect a 3D reconstruction from projections that have been generated with installations of another provider.

[0019] The 3D reconstruction center that, as a matter of course, has a suitable accounting system at its disposal for use in conjunction with the creation of the 3D datasets, and that is paid by the customers for each download, can be, for example, a producer of x-ray devices that in this way offers its customers an inexpensive possibility for an expanded use of a simpler x-ray systems. Generally most doctors that employ C-arm systems wish to create such a 3D dataset in only a few instances, and as a result it is not cost-justified to install elaborate 3D software on a standard computer networked with the C-arm installation. The inventive method allows such physicians nevertheless to be able to obtain and use a 3D dataset when needed.

[0020] Although modifications and changes may be suggested by those skilled in the art, it is the intention of the inventors to embody within the patent warranted hereon all changes and modifications as reasonably and properly come within the scope of their contribution to the art.

We claim as our invention:

1. A method for generating a three-dimensional image dataset from a plurality of two-dimensional x-ray recordings, comprising the steps of:

obtaining a plurality of 2D x-ray recordings of a subject, respectively at different projection directions, at a first location;

transmitting said plurality of 2D x-ray recordings from said first location to a reconstruction center at a second location, remote from said first location;

at said reconstruction center, making a calibration from said 2D x-ray recordings of a projection geometry needed for generating a three-dimensional volume dataset from said 2D x-ray recordings and, using said calibration and said plurality of 2D x-ray recordings, generating a 3D volume dataset; and

transmitting said 3D volume dataset from said reconstruction center at said second location to said first location.

2. A method as claimed in claim 1 comprising generating a video at said reconstruction center of said 3D volume dataset.

3. A method as claimed in claim 1 comprising generating specially rendered individual exposures of said 3D volume dataset at said reconstruction center.

4. A method as claimed in claim 1 comprising establishing an Internet connection between said first and second locations, and transmitting said plurality of 2D x-ray recording electronically from said first location to said second location via said Internet connection, and transmitting said 3D volume dataset from said second location to said first location via said Internet connection.

5. A method as claimed in claim 1 wherein the step of making a calibration at said reconstruction center comprises making an autocalibration at said reconstruction center using automatically detected natural landmarks in said plurality of two-dimensional x-ray recordings, and calculating respective point correspondences based on said natural landmarks.

6. A method as claimed in claim 5 comprising, at said reconstruction center, additionally calculating respective three-dimensional coordinates of said points and deriving projection parameters from the point correspondences.

7. A method as claimed in claim 1 wherein the step of making said calibration at said reconstruction center comprises manually detecting natural landmarks in said plurality of two-dimensional x-ray recordings, and making an autocalibration at said reconstruction center by calculating respective point correspondences based on the manually detected natural landmarks.

8. A method as claimed in claim 7 comprising, at said reconstruction center, additionally calculating respective three-dimensional coordinates of said points and deriving projection parameters from the point correspondences.

9. A method as claimed in claim 1 comprising the step of attaching detectable markers to said subject when generating said plurality of two-dimensional x-ray recordings, and wherein the step of making said calibration at said reconstruction center comprises making an autocalibration at said reconstruction center by automatically detecting said markers in said plurality of two-dimensional x-ray recordings and calculating respective point correspondences based on the automatically detected markers.

10. A method as claimed in claim 9 comprising, at said reconstruction center, additionally calculating respective three-dimensional coordinates of said points and deriving projection parameters from the point correspondences.

11. A method as claimed in claim 1 comprising transmitting a calibration sample with a known three-dimensional geometry from said first location to said reconstruction center at said second location together with said plurality of two-dimensional x-ray recordings, and at said reconstruction center, calculating said point correspondences from automatically detected point features and deriving projection parameters from said known three-dimensional geometry.

12. A method for generating a three-dimensional image dataset from a plurality of two-dimensional x-ray recordings, comprising the steps of:

obtaining a plurality of 2D x-ray recordings of a subject, respectively at different projection directions, at a first location;

transmitting said plurality of 2D x-ray recordings from said first location to a reconstruction center at a second location, remote from said first location;

at said reconstruction center, automatically calibrating a projection geometry needed for generating a three-

dimensional volume dataset from said plurality of 2D x-ray recordings and, using said projection geometry, calculating said 3D volume dataset from said plurality of two-dimensional x-ray recordings; and

transmitting said 3D volume dataset from said reconstruction center at said second location to said first location.

* * * * *